

## Labdisc Gensci Data Logger Specifications



Parameter	Labdisc Gensci
Supported Platforms	Standalone, PC, MAC, iPad Linux, Android, Chromebook
Built-in Accessible Sensors	13 sensors: Air Pressure, Ambient Temperature, Current, Distance (Motion), External Temperature, GPS, Light, Microphone, pH, Relative Humidity, Sound Level, Universal Input and Voltage
Stopwatch	0.1 second to 99:59.9 minutes
Max. Sampling Speed	100,000/s
Sampling Resolution	12-bit
Internal Data Storage	1,000,000 samples
Internal Rechargeable Battery	LiPO 3.6V
Battery Life	> 150 hours
Display	Graphical LCD 64 x 128 pixels
Keypad	Yes
Communication	USB V2.0
Wireless Communication	Bluetooth V2.0+EDR
Remote Data Collection	Yes
Automatic Sensor Testing & Calibration	Yes
Size	φ= 132, H = 45 mm
Weight	300 gr.
Temperature Range	-10 to 50 °C
Standard Compliance	CE, FCC



## **Labdisc Gensci Built-in Sensor Specifications**

Sensor Type	Max. Range	Accuracy
Air Pressure	0 to 300 kPa	±2.5 kPa
Ambient Temperature	-10 to 50 °C	±1°C
Current	-1 to 1 A	±2 %
Distance (Motion)	0.4 to 10 m	±2 %
GPS	N/A	±3 m
Light	0 to 55,000 lx	±15 %
Microphone	0 to 5 V	±2 %
рН	0 to 14 pH	±2 %
Relative Humidity	0 to 100 %RH	±3.5% (20%-80%RH)
Sound Level	56 to 95 dBa	±4 dB
Temperature	-25 to 125 °C	±2 °C
Universal Input	0 to 5 V	±2 %
Voltage	-30 to 30 V	±2 %



## **Analysis Software Specifications**

Parameter	Description
Data Retrieval	Online up to 100 samples per second, or download Labdisc stored data
Data Display	Line graphs, bar graphs, tables, meters, Google Maps
Communication	USB 2.0, Bluetooth 2.0
Data Logging Configuration	Sensor selection, sampling rate, sampling points
Graph Manipulation	Placing and moving up to two markers on the graphs, zoom in/out, graph cropping, graph color change, sensor legend (allowing graph show/hide and the selection of lines/icons for the graph samples)
<b>Graph Annotation</b>	Text and image annotations on the graph
Mathematical Functions	Derivative, linear regression, quadratic regression, FFT
Statistics	Minimum, maximum, average, standard deviation for a selected graph
Data Manipulation	Save/open experiment data, direct export to EXCEL, display hardcopy printout
Workbook	Full suite of built-in curriculum activities
Stored Experiments	Full suite of stored experiment data
Configuration	Sensor calibration, change of sensor units
Firmware Update	Ability to update the Labdisc firmware through a USB connection
OS	PC, Mac, Linux, iPad, Android, Chromebook