



Pure and Secure LLC
4120 NW 44th Street
Lincoln, NE 68524 USA
Tel: 1-800-875-5915
Website: www.mypurewater.com
Email : sales@pureandsecure.com

PURE WATER BOTTLELESS POU WATER COOLERS:

Description: A perfect complimentary product for our Pure Water Distillers and the PW Bottleless Water coolers. It will serve and meet the expectations of multi-market levels; residential and commercial.

For **residential use**, the cooler will fit in your kitchen, even in the second floor (provided that the distiller has a pump). The hot Faucet has a child safety control. There is a shut-Off valve to stop leaking and thus flooding your kitchen, basement etc.

For the **commercial market**, the distiller could be installed in a remote area and have the water pumped to the POU water cooler where the employer and employees can enjoy a refreshing cold water for the morning and during the breaks; or hot water to mix your coffee with giving you a jump start for the day. The PW-POU coolers are available in 2 original classical colors; white like the snow or charcoal like a clear sky at night. Pure Water Bottleless POU coolers are available in **Cook** and **Cold (C&C)** or **Hot** and **Cold (H&C)** temperatures.



Unique Selling Point: Optional Conversion Kit that alters the Bottleless Water Cooler into a Bottled Water Cooler

Specifications:

- Single Float System
- Plenty of Water Line
- Shut-Off Valve Included
- Easy Installation
- Child Safety Control

Cabinet:

- Quick Removal
- Durable Siding
- One Piece
- Available in:
White or Charcoal

Handle:

- Easy to Carry
- Galvanized Steel
- SS Reservoir

Water Cooler Temperature:

- Cold: 37° F - 41°
- Hot: 181° F ± 41° F



Great Compressor and Hot Tank:

- Adjustable Temperature
- Fast Cool System
- 5 Year Limited Warranty
- Automatic Reset
- Fast Drain
- Easy to Clean

Dimensions

- Width = 12.5"
- Depth = 13"
- Length = 39.75"

Weight:

- Shipping Weight = 40 lbs.

Electrical Output

- Voltage: 110V
- Power Consumption:
Cold: 110W / Hot: 450W
- Amps: Cold: 1.5A / Hot: 3.5A